

PRODUKTVELGER FOR BALANSERINGSpulver

Store lastebiler, vogntog, busser og flerbruksbiler

Dekktørrelse	Enkelt	Gram pr. pose	Tvilling	Gram pr. pose	
7.50	R 15	F	85	F	85
8	R 17.5	E	115	E	115
8,5	R 17.5	E	115	E	115
9	R 17.5	D	170	D	170
9,5	R 17.5	D	170	D	170
10	R 17.5	C	230	C	230
11	R 17.5	B	280	B	280
355/45	R 17.5	B	280	B	280
205/60	R 17.5	E	115	E	115
225/60	R 17.5	E	115	E	115
205/65	R 17.5	E	115	E	115
195/70	R 17.5	E	115	E	115
215/70	R 17.5	E	115	E	115
235/70	R 17.5	E	115	E	115
245/70	R 17.5	E	115	E	115
265/70	R 17.5	D	170	D	170
315/70	R 17.5	C	230	C	230
205/75	R 17.5	E	115	E	115
215/75	R 17.5	E	115	E	115
225/75	R 17.5	E	115	E	115
235/75	R 17.5	D	170	E	115
245/75	R 17.5	D	170	D	170
205/80	R 17.5	D	170	D	170
225/80	R 17.5	D	170	D	170
315/80	R 17.5	B	280	B	280
445/45	R 19.5	A	340	-	-
435/50	R 19.5	A	340	-	-
265/55	R 19.5	C	230	-	-
385/55	R 19.5	A	340	-	-
425/55	R 19.5	B	280	-	-
255/60	R 19.5	D	170	D	170
225/70	R 19.5	D	170	C	230
245/70	R 19.5	D	170	C	230
265/70	R 19.5	D	170	C	230
275/70	R 19.5	C	230	B	280
285/70	R 19.5	C	230	B	280
305/70	R 19.5	B	280	A	340
7.50	R 20	C	230	B	280
8.25	R 20	C	230	B	280
9.0	R 20	B	280	B	280
10.00	R 20	B	280	A	340
11.00	R 20	A	340	A	340
12.00	R 20	A	340	A	340
13.00	R 20	A	340	A	340

Dekktørrelse	Enkelt	Gram pr. pose	Tvilling	Gram pr. pose	
24	R 20.5	A + D	500	-	-
9	R 22.5	B	280	A	340
10	R 22.5	B	280	A	340
11	R 22.5	B	280	A	340
12	R 22.5	A	340	A	340
13	R 22.5	A	340	A	340
455/40	R 22.5	V (B+E)	400	-	-
315/45	R 22.5	B	280	A	340
375/45	R 22.5	A	340	-	-
435/45	R 22.5	V (B+E)	400	-	-
455/45	R 22.5	V (B+E)	400	-	-
495/45	R 22.5	A + D	500	-	-
355/50	R 22.5	A	340	-	-
375/50	R 22.5	A	340	-	-
435/50	R 22.5	W (A+E)	450	-	-
445/50	R 22.5	W (A+E)	450	-	-
295/55	R 22.5	B	280	A	340
385/55	R 22.5	A	340	-	-
455/55	R 22.5	A + D	500	-	-
265/60	R 22.5	B	280	A	340
285/60	R 22.5	B	280	A	340
295/60	R 22.5	B	280	A	340
305/60	R 22.5	B	280	A	340
315/60	R 22.5	B	280	A	340
385/65	R 22.5	"A (normal) A+E (heavy duty)"	"340 (normal) 340+115 (heavy Duty)"	-	-
425/65	R 22.5	A + D	500	-	-
445/65	R 22.5	A + D	500	-	-
255/70	R 22.5	C	230	B	280
265/70	R 22.5	C	230	B	280
275/70	R 22.5	B	280	A	340
305/70	R 22.5	B	280	A	340
315/70	R 22.5	B	280	A	340
365/70	R 22.5	V (B+E)	400	-	-
295/75	R 22.5	B	280	-	-
445/75	R 22.5	B + B	560	-	-
275/80	R 22.5	B	280	A	340
295/80	R 22.5	A	340	A	340
315/80	R 22.5	A	340	A	340
375/90	R 22.5	A + D	500	-	-

Mindre lastebiler med C- eller LT-merket dekk

Dekktørrelse	Type	Gram pr. pose	
All sizes	R 15	F	85
up to 225	R 16C	F	85
235/65	R 16C	E	115
285/65	R 16C	D	170
305/65	R 16	D	170
345/65	R 16	C	230
245/70	R 16	E	115
305/70	R 16	D	170
235/75	R 16	E	115
175/75	R 16	F	85
185/75	R 16C	F	85
195/75	R 16C	F	85
205/75	R 16C	F	85
215/75	R 16C	F	85
225/75	R 16C	F	85
245/75	R 16	E	115
265/75	R 16	E	115
285/75	R 16	D	170
295/75	R 16	D	170
315/75	R 16	C	230
215/85	R 16	F	85
225/85	R 16	E	115
235/85	R 16	E	115
245/85	R 16	E	115
255/85	R 16	D	170
265/85	R 16	D	170
305/85	R 16	C	230
225/55	R 17C	F	85
255/55	R 17C	F	85
215/60	R 17C	F	85
235/60	R 17C	E	115
205/70	R 17C	F	85
265/70	R 17	E	115
245/75	R 17	E	115
255/55	R 18	E	115
275/65	R 18	D	170
245/70	R 18	D	170
265/70	R 18	D	170
275/70	R 18	D	170

EQFX-W = 450 g EQFX-C = 230 g
 EQFX-V = 397 g EQFX-D = 170 g
 EQFX-A = 340 g EQFX-E = 115 g
 EQFX-B = 280 g EQFX-F = 85 g

Spar tid. Spar penger. Gjør det enkelt med balanseringspulver!